

## ABOUT

|                     |                         |          |
|---------------------|-------------------------|----------|
| Type of manufacture | Tufted                  | ISO 2424 |
| Width               | 400 cm / 500 cm         | EN 14159 |
| Type of surface     | Loop pile               | ISO 2424 |
| Pile material       | 100% wool               | ISO 2424 |
| Backing             | Actionback              | ISO 2424 |
| Pile weight         | ± 1095 g/m <sup>2</sup> | ISO 8543 |
| Total weight        | ± 2100 g/m <sup>2</sup> | ISO 8543 |
| Pile height         | ± 4,0 mm                | ISO 1766 |
| Total height        | ± 5,0 mm                | ISO 1765 |

## APPLICATION

|                               |                                        |                                                                                       |                         |
|-------------------------------|----------------------------------------|---------------------------------------------------------------------------------------|-------------------------|
| Use classification            | 23 residential use / 32 commercial use |  | EN 1307   ISO 10361     |
| Suitability for use on stairs | Suitable for residential use           |  | EN 1307   ISO 12951     |
| Suitability for castor chair  | Suitable for residential use           |  | EN 1307   ISO 4918      |
| Antistatic behaviour          | ≤ 2.0 kV at 25% RH                     |  | ISO 6356                |
| Thermal resistance            | ≤ 0,13 m <sup>2</sup> K/W              |  | ISO 8302                |
| Burning behaviour             | C <sub>fl</sub> -s1                    |  | EN 11925-2   ISO 9239-2 |
| Colourfastness to light       | ≥ 5                                    |  | EN 1307   ISO 105-B02   |
| Impact sound insulation       | Δ L <sub>w</sub> ≥ 25 dB               |  | EN 717-2   ISO 10140-3  |
| Comfortclass                  | LC3                                    |  | EN 1307   EN 8543       |
| Slip Resistance               | DS                                     |  | EN 14041   EN 13893     |

